

-86°C Ultra Low Temperature Freezer

FSF-86V588E

Ultra Low Temperature Freezer are specially designed to store samples products



Features

- Ambient temperature :10°C~32°C.
- Accurate Temperature control technology to make the temperature maintain -40°C~ -86°C and accuracy 0.1°C.
- Independent research and development of mixed refrigerant can make device save energy 50%.
- Better uniformity, uniformity is increased 30%.
- The single level optimization of auto cascade refrigeration system design, less refrigeration component for easy maintenance.
- 304 stainless steel inner chamber for friendly using and easy cleaning.
- VIP II PLUS technology, special narrow design for entering elevators.

Safety

- Build-in back-up battery to display temperature and to operate audible and visual alarm system for up to 72 hours without AC power.
- Visual and audible alarm system:High/low temperature,Power failure,Abnormal voltage,Sensor error,Filter screen check,Low battery,Condenser clean,High ambient temperature,Door ajar alarm
- Power failure protection: turn on delay of the cooling system when power failure,restart delay protection.
- Keyboard lock, password protection to avoid set parameter randomly.
- Special noise reduction design.

Humanized design

- 4 casters with stopper for easy moving and fixation.
- Standard 25mm test hole for easy connecting to temperature monitoring systems.
- 3 adjustable shelves for easy storing.
- Removable condenser dust gauze convenient for cleaning and maintenance.
- Removable inner door for user to defrost and clean.
- Standard USB port,USB port to read temperature and alarm conditions in recent 1 months.

Special:

Patented technology, mixed refrigerant.
Save energy up to 50%.
Wide voltage design: 187V~242V available.
Build-in back-up battery: 72 hours power failure alarm.
9 visual and audible alarms.

Performance

Temperature Range	-40~+86°C
Ambient Temperature	+10~+32°C
Controller	Microprocessor
Display	Digital Display

Electrical Data

Power Supply(V/Hz)	220/50~60; 115/60
Rated Power(W)	1500
Electrical Current(A)	9.1
Power Consumption	16.5kWh/24h
Power failure backup system	72H

Alarm

High/Low Temperature	Y
Sensor Error	Y
Power Failure	Y
Door ajar	Y
High Ambient temp.	Y
Condenser clean	Y
Low battery	Y
Filter screen check	Y
Abnormal voltage	Y

Refrigeration System

Compressor/Brand	2/SECOP
Refrigerant	Mixed
Cooling Type	Direct cooling
Defrost Type	Manual

Dimensions

Capacity	588L
Interior Size(W*D*H)	606*738*1310mm
Exterior Size(W*D*H)	880*1090*1995mm
Package Size(W*D*H)	970*1140*2190mm
N.t./G.t.(approx)	290/360kg
Loading Qty(20'/40'/40'H)	12/24/ 24

Accessories

Data Logger	Optional
Caster	4
USB port	Y
Remote alarm port	Y
RS232/485 port	Y
Inner Door/shelf	2/3
Test hole	1/25MM
CO2/LN2 back up system	Optional
Cold storage box loading QTY	40000